

# ConSeal™ CS-300

## High Performance Surface Primer



## Surface Preparation Coating and Installation Aid for Concrete and Metal Surfaces

### Applications

Installation aid for bonding preformed sealants in wet conditions or frozen concrete structures.

### Sealing Properties

CS-300 surface primer has the ability to create a bond on wet concrete surfaces. CS-300 is ideal when working in extreme weather conditions such as freezing temperatures or heavy rain.

### Physical Properties

#### Description

Color:	Clear
% Solids:	15.5% ± 1%
Solvent Type:	Hexane
Flash Point:	-25°F
Weight / Gallon:	5.87 Pounds
Dry Time @ 77°F (25°C):	15 minutes or less
Dry Time @ 40°F (4°C):	15 minutes
Clean Up:	Mineral Spirits
Coverage Per Gallon:	Approx. 300 sq ft on wet cast concrete.
Min. Storage Temperature:	32°F
Min. Application Temperature:	0°F
Surface When Dry:	Tacky

### Limited Warranty

This information is presented in good faith, but we cannot anticipate all conditions under which this information and our products, or the products of other manufactures in combination with our products, may be used. We accept no responsibility for results obtained by the application of this information or the safety and suitability of our products, either alone or in combination with other products. Users are advised to make their own tests to determine the safety and suitability of each such product or product combinations for their own purposes. It is the **users' responsibility** to satisfy himself as to the suitability and completeness of such information for this own particular use. We sell this product without warranty, and buyers and users assume all responsibility and liability for loss or damage arising from the handling and use of this product, whether used alone or in combination with other products.

*Don't Just Seal It, ConSeal It!*

© 2013 Concrete Sealants, Inc.

**Concrete Sealants, Inc.** 9325 State Route 201 ■ Tipp City, OH 45371 ■ **Toll Free** 800.332.7325  
**P.** 937.845.8776 **F.** 937.845.3587 ■ **www.conseal.com**

